
## **Model Portagard A, 12 mm**

For extremely high levels of dirt and high foot traffic.







Suitable for outdoor areas



Open mat construction



Low moisture absorption





For high foot traffic



Moderate dirt uptake



Rollable mat



3 years guarantee



Load carrying capacity up to 10kN

## Description

Portagard A is a highly flexible entrance mat design. Available in four different heights, it is a reliable solution for an extremely wide range of applications. It also has an integral micro-scraper profile.

## Colours



Black

For mat heights in mm	12
Weight (kg/m²)	12.67
Profile spacing	5 mm
Accessibility	Wheelchairs and hand trolleys
Compressive wheel load	Compressive wheel load: - area to DIN 1072 = 200 x 260 mm = 520 cm² conditions: full-surface mat coverage, appropriate substructure. 2,000 N:520 cm² = 4 N/cm², 10,000 N:520 cm² = 19 N/cm², 15,000 N:520 cm² = 29 N/cm², 20,000 N:520 cm² = 38 N/cm², 30,000 N:520 cm² = 58 N/cm², 40,000 N:520 cm² = 77 N/cm², 75,000 N:520 cm² = 144 N/cm²
Tread surface	replaceable, robust, weather-proof and profiled rubber inserts alternating with 5 mm spacers
Support chassis	Aluminium support chassis with integral microscraper bar and sound insulation underlay