



# Portagard IK

## Model Portagard IK, 22 mm

For extremely high levels of dirt and high foot traffic.



### Description

The open-base roll-up mat for functionally demanding areas. Made from replaceable, robust ribbed carpet strips in an aluminium support chassis with additional aluminium scraper profile to collect coarse dirt.

### Colours



Beige-brown



Anthracite



light grey

|                                  |   |
|----------------------------------|---|
| <b>For mat heights in mm</b>     | 22  |
| <b>Weight (kg/m<sup>2</sup>)</b> | 11.95   |
| <b>Profile spacing</b>           | 5 mm  |
| <b>Accessibility</b>             | Wheelchairs and hand trolleys   |
| <b>Compressive wheel load</b>    | Compressive wheel load: - area to DIN 1072 = 200 x 260 mm = 520 cm <sup>2</sup> . - conditions: full-surface mat coverage, appropriate substructure. 2,000 N : 520 cm <sup>2</sup> = 4 N/cm <sup>2</sup> , 10,000 N : 520 cm <sup>2</sup> = 19 N/cm <sup>2</sup> , 15,000 N : 520 cm <sup>2</sup> = 29 N/cm <sup>2</sup> , 20,000 N : 520 cm <sup>2</sup> = 38 N/cm <sup>2</sup> , 30,000 N : 520 cm <sup>2</sup> = 58 N/cm <sup>2</sup> , 40,000 N : 520 cm <sup>2</sup> = 77 N/cm <sup>2</sup> , 75,000 N : 520 cm <sup>2</sup> = 144 N/cm <sup>2</sup> |
| <b>Tread surface</b>             | replaceable, robust, highly absorbent ribbed carpet strips  |
| <b>Support chassis</b>           | Aluminium support chassis with additional aluminium scraper bar and sound insulation underlay   |



suitable for indoor areas



Suitable for covered outdoor areas



Open mat construction



High moisture absorption



For high foot traffic



Moderate dirt uptake



Scraper bar



Rollable mat



3 years guarantee



Load carrying capacity up to 20kN

Subject to technical modifications

Kafloor Mats GmbH · Johannes-Gutenberg-Platz 1 · 06773 Gräfenhainichen  
 · Telephone: +49 34953 31455 · Telefax: +49 34953 31459 · eingangsmatten@kafloor.de · www.kafloor.de